

10 578 699 90 **GROHE RAPIDO SHOWER FRAME DUO WWHRS 1 PIPE ELEMENT FOR DUO CONCEALED SHOWER INSTALLATION**



PRODUCT DESCRIPTION (1/2)

- with waste water heat recovery system (single pipe)
- for shower installations with one hand shower and a duo spray head shower
- with waste water heat recovery system
- reducing energy cost with using warmth of waste water: efficiency up to 52%
- ВКЛЮЧА:
- one heat recovery copper pipe
- pump X W / 24 V
- revision access (to be tiled) to maintain water supply and electronic components
- power supply for ceiling mount with low voltage (24 V)
- waste water connection behind shower drain
- pre-mounted rough-in set GROHE Rapido SmartBox (35 604)
- pre-mounted rough-in set 9.5 l/min for head shower (26 484)
- pre-mounted wall outlet for hand shower
- pre-mounted and insulated mixed water pipes
- for on-the-wall installations or dry-cladding
- Носеща стоманена рамка, прахово боядисана
- completely pre-assembled
- с възможност за регулиране в дълбочина
- 2 inlets at revision access height, 1/2"
- min. installation depth (from rough wall to end finish) 182-197 mm
- min. installation depth (from rough wall to frame front) 157 mm
- revision door for double plasterboard 25 mm thick
- head shower outlet height adjustable by 180 mm
- sealing fleeces
- leak test done ex factory

10 578 699 90 **GROHE RAPIDO SHOWER FRAME DUO WWHRS 1 PIPE ELEMENT FOR DUO CONCEALED SHOWER INSTALLATION**

PRODUCT DESCRIPTION (2/2)

- suitable for concealed 3-function trim sets in combination with GROHE Rapido SmartBox
- suitable for GROHE shower outlet elbows with male connection threads, 1/2"
- suitable for Rainshower SmartActive 310 2-spray head shower with 430 mm shower arm
- perfect fit for Grohtherm concealed shower systems 103 997 0000 and 103 998 0000
- for on-the-wall installation please order wall brackets 38 558 00M (sold separately, 3 sets needed)
- професионална серия